

The following SDS references the products below:

Gas Line Anti-Freeze

Vendor Item Number: PYGLA12

Manufactured By:

Niteo Products

Distributed by Kimball Midwest with the KM product-
identification number:

80-979



SAFETY DATA SHEET

Revision Date: 08/06/2015

Print Date: 09/29/2017

SDS Number: 600000000452

 Pyroil™ GASLINE ANTIFREEZE
 PYGLA12

Version: 1.1

29 CFR 1910.1200 (OSHA HazCom 2012)

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION
Product identifier

 Trade name : Pyroil™
 GASLINE ANTIFREEZE

Recommended use of the chemical and restrictions on use

Details of the supplier of the safety data sheet Niteo Products, LLC P.O. Box 191629 Dallas TX 75219 United States of America	Emergency telephone number CHEMTREC DIRECT 1-800-424-9300 Product Information 1-844-696-4836
--	---

SECTION 2. HAZARDS IDENTIFICATION
GHS Classification

Flammable liquids : Category 2
 Acute toxicity (Oral) : Category 3
 Acute toxicity (Inhalation) : Category 3
 Acute toxicity (Dermal) : Category 3
 Specific target organ systemic toxicity - single exposure : Category 1 (Central nervous system, Eyes)

GHS Label element

Hazard pictograms :   

Signal Word : Danger

Hazard Statements : Highly flammable liquid and vapor.
 Toxic if swallowed, in contact with skin or if inhaled.
 Causes damage to organs (Central nervous system, Eyes).

SAFETY DATA SHEET

Revision Date: 08/06/2015

Print Date: 09/29/2017

SDS Number: 600000000452

Pyroil™ GASLINE ANTIFREEZE
PYGLA12

Version: 1.1

Precautionary Statements

: Prevention:

- Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
- Keep container tightly closed.
- Ground/bond container and receiving equipment.
- Use explosion-proof electrical/ ventilating/ lighting/ equipment.
- Use only non-sparking tools.
- Take precautionary measures against static discharge.
- Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.
- Wash skin thoroughly after handling.
- Do not eat, drink or smoke when using this product.
- Use only outdoors or in a well-ventilated area.
- Wear protective gloves/ eye protection/ face protection.

Response:

- IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician. Rinse mouth.
- IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/ physician.
- IF exposed: Call a POISON CENTER or doctor/ physician. Take off contaminated clothing and wash before reuse.
- In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

- Store in a well-ventilated place. Keep container tightly closed.
- Store in a well-ventilated place. Keep cool.
- Store locked up.

Disposal:

- Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : Defatter

Hazardous components

Chemical Name	CAS-No.	Classification	Concentration (%)
METHANOL	67-56-1	Flam. Liq. 2; H225 Acute Tox. 3; H301 Acute Tox. 3; H331 Acute Tox. 3; H311	99.84

SAFETY DATA SHEET

Revision Date: 08/06/2015

Print Date: 09/29/2017

SDS Number: 600000000452

Pyroil™ GASLINE ANTIFREEZE
PYGLA12

Version: 1.1

		STOT SE 1; H370
--	--	-----------------

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
- If inhaled : Move to fresh air.
Call a physician or poison control centre immediately.
Keep patient warm and at rest.
If unconscious place in recovery position and seek medical advice.
- In case of skin contact : If on skin, rinse well with water.
First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.
Wash contaminated clothing before re-use.
If on clothes, remove clothes.
- In case of eye contact : Flush eyes with water as a precaution.
Remove contact lenses.
Protect unharmed eye.
If eye irritation persists, consult a specialist.
- If swallowed : Get medical attention immediately.
Rinse mouth with water.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : This product contains methanol which can cause intoxication and central nervous system depression. Methanol is metabolized to formic acid and formaldehyde. These metabolites can cause metabolic acidosis, visual disturbances and blindness. Since metabolism is required for these toxic symptoms, their onset may be delayed from 6 to 30 hours following ingestion. Ethanol competes for the same metabolic pathway and has been used to prevent methanol metabolism. Ethanol administration is indicated in symptomatic patients or at blood methanol concentrations above 20 ug/dl. Methanol is effectively removed by hemodialysis.
Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through

SAFETY DATA SHEET

Revision Date: 08/06/2015

Print Date: 09/29/2017

SDS Number: 600000000452

Pyroil™ GASLINE ANTIFREEZE
PYGLA12

Version: 1.1

the skin may include:
 stomach or intestinal upset (nausea, vomiting, diarrhea)
 irritation (nose, throat, airways)
 muscle cramps
 pain in the abdomen and lower back
 Blurred vision
 Shortness of breath
 cyanosis (causes blue coloring of the skin and nails from lack of oxygen)
 visual impairment (including blindness)
 Toxic if swallowed, in contact with skin or if inhaled
 Causes damage to organs.

Notes to physician : No hazards which require special first aid measures.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
 Water spray
 Foam
 Alcohol-resistant foam
 Carbon dioxide (CO2)
 Dry chemical

Unsuitable extinguishing media : High volume water jet

Specific hazards during firefighting : Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively.
 Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
 Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : carbon dioxide and carbon monoxide

Specific extinguishing methods :
 Product is compatible with standard fire-fighting agents.

Further information : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
 Use a water spray to cool fully closed containers.

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

SAFETY DATA SHEET

Revision Date: 08/06/2015

Print Date: 09/29/2017

SDS Number: 600000000452

Pyroil™ GASLINE ANTIFREEZE
PYGLA12

Version: 1.1

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Evacuate personnel to safe areas.
Remove all sources of ignition.
Ensure adequate ventilation.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
- Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).
- Other information : Comply with all applicable federal, state, and local regulations.
Suppress (knock down) gases/vapours/mists with a water spray jet.

SECTION 7. HANDLING AND STORAGE

- Advice on safe handling : Open drum carefully as content may be under pressure.
Avoid formation of aerosol.
Provide sufficient air exchange and/or exhaust in work rooms.
Do not breathe vapours/dust.
Do not smoke.
Container hazardous when empty.
Take precautionary measures against static discharges.
Smoking, eating and drinking should be prohibited in the application area.
For personal protection see section 8.
Dispose of rinse water in accordance with local and national regulations.
Container may be opened only under exhaust ventilation hood.
- Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
No smoking.
Electrical installations / working materials must comply with the technological safety standards.

SAFETY DATA SHEET

Revision Date: 08/06/2015

Print Date: 09/29/2017

SDS Number: 600000000452

 Pyroil™ GASLINE ANTIFREEZE
 PYGLA12

Version: 1.1

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
METHANOL	67-56-1	TWA	200 ppm	ACGIH
		STEL	250 ppm	ACGIH
		REL	200 ppm 260 mg/m3	NIOSH/GUID E
		STEL	250 ppm 325 mg/m3	NIOSH/GUID E
		PEL	200 ppm 260 mg/m3	OSHA_ TRANS
		TWA	200 ppm 260 mg/m3	TN OEL
		STEL	250 ppm 325 mg/m3	TN OEL

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
METHANOL	67-56-1	methanol	Urine	Sampling time: End of shift.	15 mg/l	
Remarks:	Background, Nonspecific					

Engineering measures : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Respiratory protection : A NIOSH-approved air-purifying respirator with an appropriate cartridge and/or filter may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits (if applicable) or if overexposure has otherwise been determined. Protection provided by air-purifying respirators is limited. Use a positive pressure, air-supplied respirator if there is any potential for uncontrolled release, exposure levels are not known or any other circumstances where an air-purifying respirator may not provide adequate protection.

Hand protection

Material : neoprene

Remarks

: The suitability for a specific workplace should be discussed with the producers of the protective gloves.

SAFETY DATA SHEET

Revision Date: 08/06/2015

Print Date: 09/29/2017

SDS Number: 600000000452

Pyroil™ GASLINE ANTIFREEZE
PYGLA12

Version: 1.1

- Eye protection : Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.
- Skin and body protection : Wear as appropriate:
impervious clothing
Safety shoes
Flame-resistant clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Discard gloves that show tears, pinholes, or signs of wear.
Wear resistant gloves (consult your safety equipment supplier).
- Hygiene measures : Avoid contact with skin, eyes and clothing.
Wash hands before breaks and immediately after handling the product.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Physical state : liquid
- Colour : colourless
- Odour : alcohol-like
- Odour Threshold : No data available
- pH : No data available
- Melting point/freezing point : No data available
- Boiling point/boiling range : 148.5 °F / 64.7 °C
(1,013.232 hPa)
Calculated Phase Transition Liquid/Gas
- Flash point : 54 °F / 12 °C
Calculated Flash Point
- Evaporation rate : No data available
- Flammability (solid, gas) : No data available
- Upper explosion limit : 36 %(V)
Calculated Explosive Limit
- Lower explosion limit : 7.3 %(V)
Calculated Explosive Limit
- Vapour pressure : 169.3164 hPa (25 °C)
Calculated Vapor Pressure
- Relative vapour density : No data available
- Relative density : No data available

SAFETY DATA SHEET

Revision Date: 08/06/2015

Print Date: 09/29/2017

SDS Number: 600000000452

Pyroil™ GASLINE ANTIFREEZE
PYGLA12

Version: 1.1

Density : 0.7923 g/cm³ (20 °C)
Calculated Density/Liquid Density

Solubility(ies)
Water solubility : No data available

Solubility in other solvents : No data available

Partition coefficient: n-
octanol/water : No data available

Thermal decomposition : No data available

Viscosity
Viscosity, dynamic : No data available

Viscosity, kinematic : No data available

Oxidizing properties : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous
reactions : Vapours may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : aluminum
Lead
sodium
Strong acids
strong bases
Strong oxidizing agents
Zinc
Peroxides

Hazardous decomposition
products : carbon dioxide and carbon monoxide
formaldehyde-like

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of : Inhalation

SAFETY DATA SHEET

Revision Date: 08/06/2015

Print Date: 09/29/2017

SDS Number: 600000000452

Pyroil™ GASLINE ANTIFREEZE
PYGLA12

Version: 1.1

exposure

Skin contact
Eye Contact
Ingestion**Acute toxicity**

Toxic if swallowed, in contact with skin or if inhaled

Components:

METHANOL:

Acute oral toxicity : LD L0 (Human): 300 mg/kg
Assessment: The component/mixture is classified as acute oral toxicity, category 3.Acute inhalation toxicity : LC 50 (Rat): 64000 ppm
Exposure time: 4 hAssessment: The component/mixture is classified as acute inhalation toxicity, category 3.
Remarks: Slightly toxic by inhalationAcute dermal toxicity : LD 50 (Rabbit): 12,800 mg/kg
Assessment: The component/mixture is classified as acute dermal toxicity, category 3.**Skin corrosion/irritation**

Not classified based on available information.

Product:

Result: Repeated exposure may cause skin dryness or cracking.

Components:

METHANOL:

Species: Rabbit

Result: Not irritating to skin

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks: Unlikely to cause eye irritation or injury.

Components:

METHANOL:

Species: Rabbit

Result: Mildly irritating to eyes

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Components:

METHANOL:

Test Type: Maximisation Test (GPMT)

Species: Guinea pig

Assessment: Does not cause skin sensitisation.

Method: OECD Test Guideline 406

SAFETY DATA SHEET

Revision Date: 08/06/2015

Print Date: 09/29/2017

SDS Number: 600000000452

Pyroil™ GASLINE ANTIFREEZE
PYGLA12

Version: 1.1

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Causes damage to organs (Central nervous system, Eyes).

Components:

METHANOL:

Target Organs: Central nervous system, Eyes

Assessment: The substance or mixture is classified as specific target organ toxicant, single exposure, category 1.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Further information

Product:

Remarks: Solvents may degrease the skin.

Components:

METHANOL:

Remarks: Central nervous system

Carcinogenicity:

IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

METHANOL:

Toxicity to fish

: LC 50 (Rainbow trout,donaldson trout (Oncorhynchus mykiss)): 18,000 - 20,000 mg/l
Exposure time: 96 h
Test Type: static test

SAFETY DATA SHEET

Revision Date: 08/06/2015

Print Date: 09/29/2017

SDS Number: 600000000452

Pyroil™ GASLINE ANTIFREEZE
PYGLA12

Version: 1.1

Toxicity to daphnia and other aquatic invertebrates : EC 50 (Water flea (Daphnia magna)): > 10,000 mg/l
Exposure time: 48 h
Test Type: static test

Persistence and degradability**Components:**

METHANOL:

Biodegradability : Biodegradation: 99 %
Exposure time: 28 d
Method: OECD Test Guideline 301D

Bioaccumulative potential**Components:**

METHANOL:

Partition coefficient: n-octanol/water : log Pow: -0.77

Mobility in soil**Components:**

No data available

Other adverse effects

No data available

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., May cause long lasting harmful effects to aquatic life.

Components:

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

General advice : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Dispose of in accordance with all applicable local, state and federal regulations.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Empty containers should be taken to an approved waste handling site for recycling or disposal.
Do not re-use empty containers.

SAFETY DATA SHEET

Revision Date: 08/06/2015

Print Date: 09/29/2017

SDS Number: 600000000452

Pyroil™ GASLINE ANTIFREEZE
PYGLA12

Version: 1.1

Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

International transport regulations

REGULATION

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.
-----------	----------------------	---------------	--------------------	---------------	------------------------------

U.S. DOT - ROAD

UN 1992	Flammable liquids, toxic, n.o.s. (METHANOL)	3	(6.1)	II	
---------	---	---	-------	----	--

U.S. DOT - RAIL

UN 1992	Flammable liquids, toxic, n.o.s. (METHANOL)	3	(6.1)	II	
---------	---	---	-------	----	--

U.S. DOT - INLAND WATERWAYS

UN 1992	Flammable liquids, toxic, n.o.s. (METHANOL)	3	(6.1)	II	
---------	---	---	-------	----	--

TRANSPORT CANADA - ROAD

UN 1992	FLAMMABLE LIQUID, TOXIC, N.O.S. (METHANOL)	3	(6.1)	II	
---------	--	---	-------	----	--

TRANSPORT CANADA - RAIL

UN 1992	FLAMMABLE LIQUID, TOXIC, N.O.S. (METHANOL)	3	(6.1)	II	
---------	--	---	-------	----	--

TRANSPORT CANADA - INLAND WATERWAYS

UN 1992	FLAMMABLE LIQUID, TOXIC, N.O.S. (METHANOL)	3	(6.1)	II	
---------	--	---	-------	----	--

INTERNATIONAL MARITIME DANGEROUS GOODS

UN 1992	FLAMMABLE LIQUID, TOXIC, N.O.S. (METHANOL)	3	(6.1)	II	
---------	--	---	-------	----	--

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

UN 1992	Flammable liquid, toxic, n.o.s. (METHANOL)	3	(6.1)	II	
---------	--	---	-------	----	--

SAFETY DATA SHEET

Revision Date: 08/06/2015

Print Date: 09/29/2017

SDS Number: 600000000452

Pyroil™ GASLINE ANTIFREEZE
PYGLA12

Version: 1.1

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

UN	1992	Flammable liquid, toxic, n.o.s. (METHANOL)	3	(6.1)	II
----	------	---	---	-------	----

MEXICAN REGULATION FOR THE LAND TRANSPORT OF HAZARDOUS MATERIALS AND WASTES

UN	1992	LIQUIDO INFLAMABLE, TOXICO, N.E.P. (METHANOL)	3	(6.1)	II
----	------	--	---	-------	----

*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

Marine pollutant	no
------------------	----

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
METHANOL	67-56-1	5000	5007.842281

SARA 311/312 Hazards : Fire Hazard
Acute Health Hazard

SARA 313 Component(s)
METHANOL 67-56-1 99.84 %

Pennsylvania Right To Know
METHANOL 67-56-1 90.00 -
100.00 %

New Jersey Right To Know
METHANOL 67-56-1 90.00 -
100.00 %

California Prop 65
WARNING! This product contains a chemical known to the State of California to cause cancer.
ETHYL BENZENE 100-41-4

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.
METHANOL 67-56-1

SAFETY DATA SHEET

Revision Date: 08/06/2015

Print Date: 09/29/2017

SDS Number: 600000000452

Pyroil™ GASLINE ANTIFREEZE
PYGLA12

Version: 1.1

The components of this product are reported in the following inventories:

- TSCA : On TSCA Inventory
- DSL : All components of this product are on the Canadian DSL.
- AICS : On the inventory, or in compliance with the inventory
- NZIOC : On the inventory, or in compliance with the inventory
- ENCS : On the inventory, or in compliance with the inventory
- KECI : On the inventory, or in compliance with the inventory
- PICCS : On the inventory, or in compliance with the inventory
- IECSC : On the inventory, or in compliance with the inventory

Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TSCA (USA)

SECTION 16. OTHER INFORMATION

Further information

Revision Date: 08/06/2015

<p>NFPA:</p> <p>Flammability</p> <p>Health</p> <p>Instability</p> <p>Special hazard.</p>	<p>HMIS III:</p> <table border="1"> <tr> <td style="background-color: blue; color: white;">HEALTH</td> <td style="text-align: center;">2*</td> </tr> <tr> <td style="background-color: red; color: white;">FLAMMABILITY</td> <td style="text-align: center;">3</td> </tr> <tr> <td style="background-color: yellow; color: black;">PHYSICAL HAZARD</td> <td style="text-align: center;">0</td> </tr> </table> <p>0 = not significant, 1 =Slight, 2 = Moderate, 3 = High 4 = Extreme, * = Chronic</p>	HEALTH	2*	FLAMMABILITY	3	PHYSICAL HAZARD	0
HEALTH	2*						
FLAMMABILITY	3						
PHYSICAL HAZARD	0						

NFPA Flammable and Combustible Liquids Classification

Flammable Liquid Class IB

Full text of H-Statements referred to under sections 2 and 3.

SAFETY DATA SHEET

Revision Date: 08/06/2015

Print Date: 09/29/2017

SDS Number: 600000000452

Pyroil™ GASLINE ANTIFREEZE
PYGLA12

Version: 1.1

H225	Highly flammable liquid and vapor.
H301	Toxic if swallowed.
H311	Toxic in contact with skin.
H331	Toxic if inhaled.
H370	Causes damage to organs.

Sources of key data used to compile the Safety Data Sheet

Internal data including own and sponsored test reports

The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

Cefic, the European Chemical Industry Council.

ESIS European Chemical Substances Information System

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Niteo's Environmental Health and Safety Department (1-844-696-4836).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists

BEI : Biological Exposure Index

CAS : Chemical Abstracts Service (Division of the American Chemical Society).

CMR : Carcinogenic, Mutagenic or Toxic for Reproduction

FG : Food grade

GHS : Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

IATA : International Air Transport Association.

IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization

ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"

IMDG : International Maritime Code for Dangerous Goods

ISO : International Organization for Standardization

logPow : octanol-water partition coefficient

LCxx : Lethal Concentration, for xx percent of test population

LDxx : Lethal Dose, for xx percent of test population.

ICxx : Inhibitory Concentration for xx of a substance

Ecxx : Effective Concentration of xx

N.O.S.: Not Otherwise Specified

OECD : Organization for Economic Co-operation and Development

OEL : Occupational Exposure Limit

P-Statement : Precautionary Statement

PBT : Persistent , Bioaccumulative and Toxic

PPE : Personal Protective Equipment

STEL : Short-term exposure limit

STOT : Specific Target Organ Toxicity

TLV : Threshold Limit Value

TWA : Time-weighted average

vPvB : Very Persistent and Very Bioaccumulative

WEL : Workplace Exposure Level

SAFETY DATA SHEET

Revision Date: 08/06/2015

Print Date: 09/29/2017

SDS Number: 600000000452

Pyroil™ GASLINE ANTIFREEZE
PYGLA12

Version: 1.1

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act

DOT : Department of Transportation

FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act

HMIRC : Hazardous Materials Information Review Commission

HMIS : Hazardous Materials Identification System

NFPA : National Fire Protection Association

NIOSH : National Institute for Occupational Safety and Health

OSHA : Occupational Safety and Health Administration

PMRA : Health Canada Pest Management Regulatory Agency

RTK : Right to Know

WHMIS : Workplace Hazardous Materials Information System