Safety Data Sheet

Date of issue: 08/07/2025 Revised On 08/07/2025

1 Identification of the substance and manufacturer

Trade name: **EQUIPMENT YELLOW**

Other means of identification

Product code: 80-1153

Article category

Paint and coatings application. Recommended use:

Any that differs from the recommended use. Uses advised against: Manufacturer/Supplier:

Kimball Midwest 4800 Roberts Road Columbus, OH 43228

800-233-1294

www.kimballmidwest.com Emergency telephone number: ChemTrec: 800-424-9300

2 Hazard(s) identification

Classification of the substance or mixture

Flammable liquids 3 H226 Flammable liquid and vapor. Eye irritation 2A H319 Causes serious eye irritation.

H351 Suspected of causing cancer. Route of exposure: Inhalation. Carcinogenicity 2

Specific target organ toxicity (repeated exposure) 2 H373 May cause damage to organs through prolonged or repeated exposure.

Additional information: **GHS Hazard pictograms**



GHS02 GHS07 GHS08

Warning Signal word

Hazard statements Flammable liquid and vapor. Causes serious eye irritation.

Suspected of causing cancer. Route of exposure: Inhalation.

May cause damage to organs through prolonged or repeated exposure.

Precautionary statements Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Keep container tightly closed.

Ground / bond container and receiving equipment.

Use explosion-proof [electrical/ventilating/lighting] equipment.

Use non-sparking tools.

Take action to prevent static discharge.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.
Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
Wear protective gloves/protective clothing/eye protection/face protection.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.
IF exposed or concerned: Get medical advice/attention. Get medical advice/attention if you feel unwell.

If eye irritation persists: Get medical advice/attention.
In case of fire: Use CO2, powder or water spray to extinguish.
Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

3 Composition/information on ingredients

Chemical characterization: Mixtures

Chemical Description: This product is a mixture of the substances listed below with nonhazardous additions

| | | This product is a mixture of this cubotaneous notice below with normazar | acac additions. |
|-----------------------|------------|--|-----------------|
| Dangerous components: | | components: | |
| | 64742-47-8 | Mineral Spirits | 15-25% |
| | 7727-43-7 | barium sulfate | 15-25% |
| | 108-65-6 | PM acetate | 1-5% |
| | 1330-20-7 | xylene (mix) | 1-5% |
| | 64742-48-9 | Naphtha, hydrotreated heavy | 1-5% |

4 First-aid measures

After skin contact: Remove contaminated clothing. Wash exposed area with soap and water.

After eye contact: Rinse opened eye for several minutes under running water.

After swallowing: Rinse mouth with water. Do not induce vomiting

Most important symptoms and

effects: No further relevant information available.

(Contd. on page 2)

Safety Data Sheet

Date of issue: 08/07/2025 Revised On 08/07/2025

Trade name: EQUIPMENT YELLOW

(Contd. of page 1)

Indication of any immediate medical

No further relevant information available. attention needed:

5 Fire-fighting measures

Special hazards: No further relevant information available. Protective equipment for

firefighters: No special measures required.

6 Accidental release measures

Personal precautions, protective equipment and emergency

procedures:

Not required. Methods and material for

containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

7 Handling and storage

Precautions for safe handling Use only in well ventilated areas.

Storage requirements: Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions.

Store lockéd up.

8 Exposure controls/personal protection

Components with limit values that require monitoring at the workplace:

7727-43-7 barium sulfate

Long-term value: 15* 5** mg/m³ *total dust **respirable fraction PEL (USA)

REL (USA) Long-term value: 10* 5** mg/m³ *total dust **respirable fraction

Long-term value: 5* mg/m3 TLV (USA) *inhalable fraction; E

108-65-6 PM acetate

WEEL (USA) Long-term value: 50 ppm

1330-20-7 xylene (mix)

PEL (USA) Long-term value: 435 mg/m³, 100 ppm Short-term value: 655 mg/m³, 150 ppm Long-term value: 435 mg/m³, 100 ppm REL (USA)

TLV (USA) Long-term value: 20 ppm

BEI, A4

111-76-2 Glycol Ether EB

Long-term value: 240 mg/m³, 50 ppm PEL (USA)

REL (USA) Long-term value: 24 mg/m³, 5 ppm Skin

Long-term value: 97 mg/m³, 20 ppm TLV (USA)

BEI, A3

Ingredients with biological limit values:

1330-20-7 xylene (mix)

BEI (USA) 1.5 g/g creatinine

Medium: urine

Time: end of shift

Parameter: Methylhippuric acids

111-76-2 Glycol Ether EB

BEI (USA) 200 mg/g creatinine Medium: urine

Time: end of shift

Parameter: Butoxyacetic acid (BAA) (with hydrolysis)

Hygienic protection: Wash hands after use.

Do not eat or drink while working.

Breathing equipment: Not required.

Hand protection: Nitrile gloves.

The glove material must be impermeable and resistant to the substance.

Tightly sealed goggles Eye protection:

9 Physical and chemical properties

Physical state Liquid

Odor:

Not determined. Odor threshold: Melting point/Melting range Undetermined.

(Contd. on page 3)

(Contd. of page 2)

Safety Data Sheet

Date of issue: 08/07/2025 Revised On 08/07/2025

Trade name: EQUIPMENT YELLOW

Boiling point: Flammability: 175 °C (347 °F) Flammable.

Lower Explosion Limit: 0.5 Vol % 6.5 Vol % 40 °C (104 °F) Upper Explosion Limit: Flash point: Flammability (solid, gas): Flammable. Decomposition temperature: Not determined. pH-value: Viscosity: Not determined. Not determined.

Vapor pressure: Relative Density:

Solubility:

Vapor density Not determined. Particle characteristics Not applicable.

Appearance: Liquid.

Ignition temperature: Product is not self-igniting.

Danger of explosion: In use, may form flammable/explosive vapour-air mixture.

Not determined.

Not determined.

Water: 0.0 %

Evaporation rate Not determined. Partition coefficient: n-octonal/water: Not determined.

LD/LC50 values that are relevant for classification:

10 Stability and reactivity

Reactivity:

Conditions to avoid: No decomposition if used according to specifications.

Possibility of hazardous reactions: No dangerous reactions known.

Incompatible materials: No further relevant information available. Hazardous decomposition: No dangerous decomposition products known.

11 Toxicological information

| 108-65-6 PM acetate | | | | | |
|---------------------|--|----------------------|--|--|--|
| Oral | LD50 | 8,500 mg/kg (rat) | | | |
| | | 35.7 mg/l (rat) | | | |
| 1330-20-7 | xylene (m | nix) | | | |
| Oral | LD50 | 8,700 mg/kg (rat) | | | |
| Dermal | LD50 | 2,000 mg/kg (rabbit) | | | |
| Inhalative | LC50/4 h | 6,350 mg/l (rat) | | | |
| 64742-48- | 64742-48-9 Naphtha, hydrotreated heavy | | | | |
| Oral | LD50 | >5,000 mg/kg (rat) | | | |
| Dermal | LD50 | >3,000 mg/kg (rab) | | | |
| 111-76-2 (| 111-76-2 Glycol Ether EB | | | | |
| Oral | LD50 | 1,200 mg/kg (ATE) | | | |
| | | 1,480 mg/kg (rat) | | | |

Inhalative LC50/4 h 3 mg/l (ATE) Information on toxicological effects: No data available. Skin effects: No irritant effect. Eye effects: No irritating effect.

400 mg/kg (rab)

Sensitization: No sensitizing effects known.

12 Ecological information

LD50

Dermal

Aquatic toxicity: Hazardous for water, do not empty into drains.

Persistence and degradability: The product is degradable after prolonged exposure to natural weathering processes.

Other information: This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's),

perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), per and polyfluoroalkyl substances (PFA's), or chlorinated solvents.

Bioaccumulative potential: No further relevant information available. Mobility in soil: No further relevant information available. Other adverse effects: No further relevant information available.

13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

Recommendation: Completely empty cans should be recycled. Recommended cleansing agent: Water, if necessary with cleansing agents.

Safety Data Sheet

Date of issue: 08/07/2025 Revised On 08/07/2025

Trade name: EQUIPMENT YELLOW

(Contd. of page 3)

14 Transport information

UN-Number

DOT UN1263 DOT Paint

ADR 1263 PAINT (vapour pressure at 50°C not more than 110 kPa) 3 Flammable liquids

Transport hazard class(es): Class

Special marking (IATA):

Packaging Group:

Warning: Flammable liquids Special precautions for user:

EMS Number: F-E,<u>S-E</u> В **Stowage Category**

UN 1263 PAINT (VAPOUR PRESSURE AT 50°C NOT MORE THAN 110 KPA), 3, II **UN "Model Regulation":**

15 Regulatory information

SARA Section 355 (extremely hazardous substances):

None of the ingredients in this product are listed.

SARA Section 313 (Specific toxic chemical listings):

7727-43-7 barium sulfate 1330-20-7 xylene (mix)

Toxic Substances Control Act

(TSCA):

Canadian Domestic Substances List

(DSL):

All ingredients are listed or exempted. Consumer Product Safety

Comission (CPSC): This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

California Proposition 65 chemicals known to cause cancer:

13463-67-7 titanium dioxide

100-41-4 ethyl benzene

Prop 65 chemicals known to cause birth defects or reproductive harm:

None of the ingredients is listed.

7727-43-7 barium sulfate D, CBD(inh), NL(oral)

All ingredients are found on the inventory list of substances.

1330-20-7 xylene (mix)

16 Other information

Contact: Regulatory Affairs